Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No.: 173492
V007.1
Revision: 15.10.2020
printing date: 24.09.2021
Replaces version from: 05.02.2019

Loctite 8007

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier
Loctite 8007

1.2. Relevant identified uses of the substance or mixture and uses advised against
Intended use:
Lubricant

1.3. Details of the supplier of the safety data sheet
Henkel Ltd
Adhesives
Wood Lane End
HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000
Fax-no.: +44 (1442) 278071

ua-productsafety.uk@henkel.com

1.4. Emergency telephone number
24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Flammable aerosols	Category 1
H222 Extremely flammable aerosol.	
H229 Pressurized container: May burst if heated.	
Skin irritation	Category 2
H315 Causes skin irritation.	
Specific target organ toxicity - single exposure	Category 3
H336 May cause drowsiness or dizziness.	
Target organ: Central nervous system	
Chronic hazards to the aquatic environment	Category 2
H411 Toxic to aquatic life with long lasting effects.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains pentane

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Signal word: Danger

Hazard statement:
H222 Extremely flammable aerosol.
H229 Pressurized container: May burst if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statement:
P251 Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P211 Do not spray on an open flame or other ignition source.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P102 Keep out of reach of children.

Precautionary statement: Prevention
P261 Avoid breathing spray.
P273 Avoid release to the environment.

Precautionary statement: Response
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P337+P313 If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

None if used properly.
Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General chemical description:
Lubricant

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Butane, n- (< 0.1 % butadiene) 106-97-8	203-448-7 01-2119474691-32	25- < 50 %	Flam. Gas 1 H220 Press. Gas H280
pentane 109-66-0	203-692-4 01-2119459286-30	10- < 25 %	Flam. Liq. 2 H225 Asp. Tox. 1 H304 STOT SE 3 H336 Aquatic Chronic 2 H411
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	927-510-4 01-2119475515-33	10- < 25 %	Asp. Tox. 1 H304 Skin Irrit. 2 H315 Flam. Liq. 2 H225 STOT SE 3; Inhalation H336 Aquatic Chronic 2 H411
Propane 74-98-6	200-827-9 01-2119486944-21	2,5- < 10 %	Flam. Gas 1 H220 Press. Gas H280
Copper 7440-50-8	231-159-6 01-2119480154-42	2,5- < 10 %	Aquatic Acute 1 H400 Aquatic Chronic 3 H412
Calcium dihydroxide 1305-62-0	215-137-3 01-2119475151-45	1- < 2,5 %	Skin Irrit. 2; Dermal H315 Eye Dam. 1 H318 STOT SE 3; Inhalation H335

For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:
Rinse with running water and soap.
Seek medical advice.

Eye contact:
Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:
Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.
Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed
SKIN: Redness, inflammation.

EYE: Irritation, conjunctivitis.

Vapors may cause drowsiness and dizziness.

4.3. Indication of any immediate medical attention and special treatment needed
See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media
Suitable extinguishing media:
Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:
High pressure waterjet

5.2. Special hazards arising from the substance or mixture
In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO2) can be released.

5.3. Advice for firefighters
Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:
In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Avoid contact with skin and eyes.
Ensure adequate ventilation.
Wear protective equipment.

6.2. Environmental precautions
Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up
For small spills wipe up with paper towel and place in container for disposal.
For large spills absorb onto inert absorbent material and place in sealed container for disposal.
Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections
See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling
Use only in well-ventilated areas.
Vapours should be extracted to avoid inhalation.
Keep away from sources of ignition - no smoking.
Avoid skin and eye contact.
See advice in section 8

Hygiene measures:
Good industrial hygiene practices should be observed.
Do not eat, drink or smoke while working.
Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities
Ensure good ventilation/extraction.
Store in a cool, well-ventilated place.
Keep away from heat and direct sunlight.
Refer to Technical Data Sheet

7.3. Specific end use(s)
Lubricant

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m³	Value type	Short term exposure limit category / Remarks	Regulatory list
Butane 106-97-8 [BUTANE]	600	1.450	Time Weighted Average (TWA):		EH40 WEL
Butane 106-97-8 [BUTANE]	750	1.810	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
Pentane 109-66-0 [PENTANE]	600	1.800	Time Weighted Average (TWA):		EH40 WEL
Pentane 109-66-0 [PENTANE]	1.000	3.000	Time Weighted Average (TWA):	Indicative	ECTLV
Copper 7440-50-8 [COPPER, FUME]		0,2	Time Weighted Average (TWA):		EH40 WEL
Copper 7440-50-8 [COPPER, INHALABLE DUSTS AND MISTS (AS CU)]		1	Time Weighted Average (TWA):		EH40 WEL
Copper 7440-50-8 [COPPER, INHALABLE DUSTS AND MISTS (AS CU)]		2	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
Calcium dihydroxide 1305-62-0 [CALCIUM HYDROXIDE]		5	Time Weighted Average (TWA):		EH40 WEL
Calcium dihydroxide 1305-62-0 [CALCIUM DIHYDROXIDE (RESPIRABLE FRACTION)]		4	Short Term Exposure Limit (STEL):	Indicative	ECTLV
Calcium dihydroxide 1305-62-0 [CALCIUM DIHYDROXIDE (RESPIRABLE FRACTION)]		1	Time Weighted Average (TWA):	Indicative	ECTLV
Calcium dihydroxide 1305-62-0 [CALCIUM HYDROXIDE (RESPIRABLE FRACTION)]		1	Time Weighted Average (TWA):		EH40 WEL
Calcium dihydroxide 1305-62-0 [CALCIUM HYDROXIDE (RESPIRABLE FRACTION)]		4	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL

Occupational Exposure Limits

Valid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m³	Value type	Short term exposure limit category / Remarks	Regulatory list
Butane 106-97-8 [N-BUTANE]	1.000		Short Term Exposure Limit (STEL):	15 minutes	IR_OEL
Pentane 109-66-0 [PENTANE]	1.000	3.000	Time Weighted Average (TWA):	Indicative	ECTLV
Pentane 109-66-0 [PENTANE]	1.000	3.000	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
Copper 7440-50-8 [COPPER]		0,2	Time Weighted Average (TWA):		IR_OEL

Copper 7440-50-8 [COPPER]		1	Time Weighted Average (TWA):		IR_OEL
Calcium dihydroxide 1305-62-0 [CALCIUM DIHYDROXIDE (RESPIRABLE FRACTION)]		4	Short Term Exposure Limit (STEL):	Indicative	ECTLV
Calcium dihydroxide 1305-62-0 [CALCIUM DIHYDROXIDE (RESPIRABLE FRACTION)]		1	Time Weighted Average (TWA):	Indicative	ECTLV
Calcium dihydroxide 1305-62-0 [CALCIUM DIHYDROXIDE (RESPIRABLE FRACTION)]		4	Short Term Exposure Limit (STEL):	15 minutes Indicative OELV	IR_OEL
Calcium dihydroxide 1305-62-0 [CALCIUM DIHYDROXIDE (RESPIRABLE FRACTION)]		1	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
Calcium dihydroxide 1305-62-0 [CALCIUM DIHYDROXIDE]		4	Short Term Exposure Limit (STEL):	15 minutes Indicative OELV	IR_OEL
Calcium dihydroxide 1305-62-0 [CALCIUM DIHYDROXIDE]		1	Time Weighted Average (TWA):	Indicative OELV	IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
pentane 109-66-0	aqua (freshwater)		0,23 mg/l				
pentane 109-66-0	aqua (marine water)		0,23 mg/l				
pentane 109-66-0	aqua (intermittent releases)		0,88 mg/l				
pentane 109-66-0	sediment (freshwater)				1,2 mg/kg		
pentane 109-66-0	sediment (marine water)				1,2 mg/kg		
pentane 109-66-0	Soil				0,55 mg/kg		
pentane 109-66-0	sewage treatment plant (STP)		3,6 mg/l				
Copper 7440-50-8	Soil				65 mg/kg		
Copper 7440-50-8	sewage treatment plant (STP)		230 µg/l				
Copper 7440-50-8	sediment (marine water)				676 mg/kg		
Copper 7440-50-8	aqua (freshwater)		7,8 µg/l				
Copper 7440-50-8	aqua (marine water)		5,2 µg/l				
Copper 7440-50-8	sediment (freshwater)				87 mg/kg		
Calcium dihydroxide 1305-62-0	aqua (freshwater)		0,49 mg/l				
Calcium dihydroxide 1305-62-0	aqua (marine water)		0,32 mg/l				
Calcium dihydroxide 1305-62-0	aqua (intermittent releases)		0,49 mg/l				
Calcium dihydroxide 1305-62-0	sewage treatment plant (STP)		3 mg/l				
Calcium dihydroxide 1305-62-0	Soil				1080 mg/kg		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
pentane 109-66-0	Workers	dermal	Long term exposure - systemic effects		432 mg/kg	
pentane 109-66-0	Workers	inhalation	Long term exposure - systemic effects		3000 mg/m3	
pentane 109-66-0	General population	dermal	Long term exposure - systemic effects		214 mg/kg	
pentane 109-66-0	General population	inhalation	Long term exposure - systemic effects		643 mg/m3	
pentane 109-66-0	General population	oral	Long term exposure - systemic effects		214 mg/kg	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	Workers	dermal	Long term exposure - systemic effects		300 mg/kg	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	Workers	inhalation	Long term exposure - systemic effects		2085 mg/m3	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	General population	dermal	Long term exposure - systemic effects		149 mg/kg	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	General population	oral	Long term exposure - systemic effects		149 mg/kg	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	General population	inhalation	Long term exposure - systemic effects		447 mg/m3	
Copper 7440-50-8	Workers	dermal	Acute/short term exposure - systemic effects		273 mg/kg	
Copper 7440-50-8	General population	inhalation	Acute/short term exposure - local effects		1 mg/m3	
Copper 7440-50-8	General population	inhalation	Long term exposure - local effects		1 mg/m3	
Copper 7440-50-8	General population	dermal	Acute/short term exposure - systemic effects		273 mg/kg	
Copper 7440-50-8	Workers	dermal	Long term exposure - systemic effects		137 mg/kg	
Copper 7440-50-8	General population	dermal	Long term exposure - systemic effects		137 mg/kg	
Copper 7440-50-8	General population	oral	Long term exposure - systemic effects		0,041 mg/kg	
Calcium dihydroxide 1305-62-0	Workers	Inhalation	Acute/short term exposure - local effects		4 mg/m3	
Calcium dihydroxide 1305-62-0	Workers	Inhalation	Long term exposure - local effects		1 mg/m3	
Calcium dihydroxide 1305-62-0	General population	Inhalation	Acute/short term exposure - local effects		4 mg/m3	
Calcium dihydroxide 1305-62-0	General population	Inhalation	Long term exposure - local effects		1 mg/m3	

Biological Exposure Indices:
None

8.2. Exposure controls:

Engineering controls:
Ensure good ventilation/extraction.

Respiratory protection:
Use only in well-ventilated areas.
An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area
Filter type: A (EN 14387)

Hand protection:
Chemical-resistant protective gloves (EN 374).
Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:
Wear protective glasses.
Protective eye equipment should conform to EN166.

Skin protection:
Wear suitable protective clothing.
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	aerosol dark orange
Odor	characteristic
Odour threshold	No data available / Not applicable
pH	Not applicable
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	35 - 36 °C (95 - 96.8 °F)
Flash point	-97 °C (-142.6 °F)
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable
Explosive limits	
lower	0,60 %(V)
upper	10,9 %(V)
Vapour pressure (20 °C (68 °F))	2100 hPa
Relative vapour density:	No data available / Not applicable

Density (20 °C (68 °F))	0,693 g/cm3
Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable
Solubility (qualitative) (Solvent: Water)	Not miscible
Solubility (qualitative) (Solvent: Acetone)	Miscible
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

9.2. Other information

Ignition temperature	215 °C (419 °F)

SECTION 10: Stability and reactivity

10.1. Reactivity
Reacts with strong oxidants.

10.2. Chemical stability
Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions
See section reactivity

10.4. Conditions to avoid
Stable under normal conditions of storage and use.

10.5. Incompatible materials
See section reactivity.

10.6. Hazardous decomposition products
carbon oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	LD50	> 5.840 mg/kg	rat	not specified
Copper 7440-50-8	LD50	> 2.500 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
Calcium dihydroxide 1305-62-0	LD50	> 7.340 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	LD50	> 2.800 mg/kg	rat	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
Copper 7440-50-8	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Calcium dihydroxide 1305-62-0	LD50	> 2.500 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Butane, n- (< 0.1 % butadiene) 106-97-8	LC50	274200 ppm	gas	4 h	rat	not specified
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	LC50	> 23,3 mg/l	vapour	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	Acute toxicity estimate (ATE)	23,31 mg/l				Expert judgement
Propane 74-98-6	LC50	> 800000 ppm	gas	15 min	rat	not specified
Copper 7440-50-8	LC50	> 5,11 mg/l	dust/mist	4 h	rat	OECD Guideline 436 (Acute Inhalation Toxicity: Acute Toxic Class (ATC) Method)

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
pentane 109-66-0	not irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Copper 7440-50-8	not irritating		rabbit	EU Method B.4 (Acute Toxicity: Dermal Irritation / Corrosion)
Calcium dihydroxide 1305-62-0	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	not irritating		rabbit	other guideline:
Copper 7440-50-8	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Calcium dihydroxide 1305-62-0	Category 1 (irreversible effects on the eye)		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Copper 7440-50-8	not sensitising	Guinea pig maximisation test	guinea pig	EU Method B.6 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Butane, n- (< 0.1 % butadiene) 106-97-8	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Butane, n- (< 0.1 % butadiene) 106-97-8	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Propane 74-98-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Propane 74-98-6	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Copper 7440-50-8	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Calcium dihydroxide 1305-62-0	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Butane, n- (< 0.1 % butadiene) 106-97-8	negative			Drosophila melanogaster	not specified
Butane, n- (< 0.1 % butadiene) 106-97-8	negative	inhalation: gas		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Propane 74-98-6	negative			Drosophila melanogaster	not specified
Propane 74-98-6	negative	inhalation: gas		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Copper 7440-50-8	negative	oral: gavage		mouse	EU Method B.12 (Mutagenicity
Copper 7440-50-8	negative	oral: gavage		rat	equivalent or similar to OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)

Carcinogenicity

No data available.

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Butane, n- (< 0.1 % butadiene) 106-97-8	NOAEL P 21,4 mg/l NOAEL F1 21,4 mg/l	screening	inhalation: gas	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Propane 74-98-6	NOAEL P 21,6 mg/l NOAEL F1 21,6 mg/l	screening	inhalation: gas	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Copper 7440-50-8	NOAEL P 1500 ppm NOAEL F1 1000 ppm NOAEL F2 1000 ppm	two-generation study	oral: feed	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)
Copper 7440-50-8	NOAEL P 1000 ppm NOAEL F1 1000 ppm NOAEL F2 1000 ppm	two-generation study	oral: feed	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Butane, n- (< 0.1 % butadiene) 106-97-8		inhalation: gas	28 d	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Propane 74-98-6		inhalation: gas	28 d 6 h/d, 7 d/w	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Copper 7440-50-8	NOAEL 1000 ppm	oral: feed	92 d 7 d/w	rat	EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)

Aspiration hazard:

The mixture is classified based on Viscosity data.

Hazardous substances CAS-No.	Viscosity (kinematic) Value	Temperature	Method	Remarks
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	0,5 mm2/s	20 °C	not specified	

SECTION 12: Ecological information

General ecological information:
Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Butane, n- (< 0.1 % butadiene) 106-97-8	LC50	27,98 mg/l	96 h		not specified
pentane 109-66-0	LC50	> 0,1 mg/l		Trout family (Salmonidae)	not specified
Copper 7440-50-8	LC50	0,193 mg/l	96 h	Pimephales promelas	other guideline:
Copper 7440-50-8	NOEC	0,188 mg/l	30 d	Perca fluviatilis	OECD Guideline 204 (Fish, Prolonged Toxicity Test: 14-day Study)
Calcium dihydroxide 1305-62-0	LC50	50,6 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Butane, n- (< 0.1 % butadiene) 106-97-8	EC50	14,22 mg/l	48 h		not specified
pentane 109-66-0	EC50	9,74 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	EC50	3 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Copper 7440-50-8	EC50	> 0,1 - 1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Calcium dihydroxide 1305-62-0	EC50	49,1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	NOEC	0,17 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Copper 7440-50-8	NOEC	> 0,1 - 1 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Calcium dihydroxide 1305-62-0	NOEC	32 mg/l	14 d	Crangon septemspinosa	OECD Guideline 202 (Daphnia sp. Chronic Immobilisation Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Butane, n- (< 0.1 % butadiene) 106-97-8	EC50	7,71 mg/l	96 h		not specified
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	EL50	29 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	NOELR	6,3 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Copper 7440-50-8	EC50	> 0,1 - 1 mg/l	72 h	not specified	OECD Guideline 201 (Alga, Growth Inhibition Test)
Copper 7440-50-8	NOEC	> 0,1 - 1 mg/l	72 h	not specified	OECD Guideline 201 (Alga, Growth Inhibition Test)
Calcium dihydroxide 1305-62-0	EC50	184,57 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Calcium dihydroxide 1305-62-0	NOEC	48 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Copper 7440-50-8	EC50	> 0,1 - 1 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Calcium dihydroxide 1305-62-0	EC20	229,2 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
pentane 109-66-0	readily biodegradable	aerobic	87 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	readily biodegradable	aerobic	98 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

The product evaporates readily.

Hazardous substances CAS-No.	LogPow	Temperature	Method
pentane 109-66-0	3,45	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT/ vPvB
Butane, n- (< 0.1 % butadiene) 106-97-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
pentane 109-66-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Propane 74-98-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Copper 7440-50-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Calcium dihydroxide 1305-62-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:
Do not empty into drains / surface water / ground water.
Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:
After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.
Disposal must be made according to official regulations.

Waste code

14 06 03 - other solvents and solvent mixtures
The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number

ADR	1950
RID	1950
ADN	1950
IMDG	1950
IATA	1950

14.2. UN proper shipping name

ADR	AEROSOLS
RID	AEROSOLS
ADN	AEROSOLS
IMDG	AEROSOLS (Solvent Naphtha (Petroleum), Light Aromatic,Pentane)
IATA	Aerosols, flammable

14.3. Transport hazard class(es)

ADR	2.1
RID	2.1
ADN	2.1
IMDG	2.1
IATA	2.1

14.4. Packing group

ADR	
RID	
ADN	
IMDG	
IATA	

14.5. Environmental hazards

ADR	Environmentally Hazardous
RID	Environmentally Hazardous
ADN	Environmentally Hazardous
IMDG	Marine pollutant
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable Tunnelcode: (D)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content (2010/75/EC) 70,3 %

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapor.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H400 Very toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel´s Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,
Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.